

Amendments to the Specification

Please replace the paragraph [0014] and [0015] with the following amended paragraph:

[0014] In assembly, the head portions 26 of the fixing members 24 ~~engaged with the pillars 12~~ get through the bigger zone 63 of the mounting opening 22. Then the bezel 10 is moved to make the ~~[[head]]~~ fixing portions ~~[[26]]~~ 28 of the fixing members 24 slide into the smaller zone 65 of the mounting openings 22. Rotate the bezel 10 until the hooks 14 along the side of the bezel 10 are engaged in the fixing slots 42 along the front panel 62 and the barbs 16 of the hooks 14 tightly clip an edge of the fixing slots 42 on the front panel 62.

[0015] In disassembly, break off the bezel 10 from the side where hooks 14 are located detaching the hooks 14 from the fixing slots 42 of the chassis 60. Then the bezel 10 is moved to make the ~~[[head]]~~ fixing portion ~~[[26]]~~ 28 slide out of the smaller zone 65 of the mounting openings 22 arriving the bigger zone 63 of the mounting openings 22. When the head portions 26 of the fixing members 24 retreat from the bigger zone 63 of the mounting opening 22, Thereby, disassembling the bezel 10 is thereby detached from the front panel 62 of the chassis 60.